



DIRECT | INDIRECT - SUSPENDED


Huntington 1

Brilliant by Design™, minimalistic aesthetic combined with our innovative Microstructure EdgeTech Optics (MEO)™ will bring your vision to light. The innovative MEO™ design utilizes high efficiency microstructure lenses and light guide plates for high optical extraction and precise light management.

FEATURES

- Innovative Microstructure EdgeTech Optics™ delivers unparalleled optic control and exceptional performance with seamless illumination and uniformity. Specify Batwing, Glare Control, Diffused (Lambertian) or Wall Wash Optics.
- MEO™ allows for minimalistic 1.5" Aperture fixtures with extremely low profiles.
- PRO optics available with Asymmetric, Wide and Narrow distributions.
- Individually controlled Direct and Indirect MEO™ optics and lumen Outputs.
- Innovative Toolless "Push to Eject" system allows for easy installation and serviceability.
- Individual fixture lengths and seamless continuous rows with no lens breaks, pixilation or hotspots up to 400 feet.
- Aircraft Cable or 361° locking Aircraft Cable Rotational mounting.
- Integral Driver, Remote Driver, In-Canopy Driver and In-Canopy Emergency Driver options.
- Specified Lumen Outputs (SLO) available
- Proudly crafted in Huntington Beach, CA - USA.


HUNTINGTON 1 LINEUP



SUSPENDED
DIRECT | INDIRECT



SUSPENDED



RECESSED



SURFACE



WALL | ARM



WALL | ARM
DIRECT | INDIRECT

PERFORMANCE OVERVIEW

4' Huntington 1 Direct Indirect - 3500K 80CRI				
Lumen Output	LL (Low)	ML (Medium)	HL (High)	SLO* (Specified)
Direct Delivered Lumens	772	1908	3760	772-5920
Indirect Delivered Lumens	772	1908	3760	772-5920
Consumed Wattage (Total)	15	36	76	14.6-131.1
Efficacy (lm/W)	105	105	99	90-105
SDCM	3	3	3	3

*Specified Lumen Output (SLO) available in customizable lumen configurations (896 lm - 6852 lm). See SLO Configurator at ExtantLighting.com



Ordering Information

PROJECT _____ TYPE _____
PRODUCT _____ QTY _____

Product Family	Driver Location	Length	Direct Lumen Output
HTGDU-1P Huntington Series Direct Indirect 1.5" Aperture (Suspended)	<input type="checkbox"/> TD Integral Driver <input type="checkbox"/> RD Remote Driver <input type="checkbox"/> CD In-Canopy Driver *Decorative open ceiling remote driver boxes available. Contact factory for details.	<input type="checkbox"/> ___ * Specify length in 1 foot increments <input type="checkbox"/> R_x_x Rectangle <input type="checkbox"/> L_x_x L Pattern <input type="checkbox"/> U_x_x_x U Pattern <input type="checkbox"/> CP Custom Pattern *Minimum Integral Driver length is 2'. Minimum Remote or In Canopy Driver can be shorter, consult factory. *Custom length fixtures can be ordered in 3" increments. *Any length over 8' requires multiple fixture segments.	<input type="checkbox"/> DLL Low (193 l/ft @ 1.84 W)* <input type="checkbox"/> DML Medium (477 l/ft @ 4.55 W)* <input type="checkbox"/> DHL High (940 l/ft @ 9.46 W)* <input type="checkbox"/> SLO-xx **Specified Lumen Output available. *Delivered lumen output & consumed wattage based on "MEODF 835" (80 CRI - 3500K). See SLO Configurator for alternate outputs. **See SLO Configurator at ExtantLighting.com for appropriate "xx" output.

Direct Optics	Indirect Lumen Output	Indirect Optics	Color Temp	Voltage
MEO <input type="checkbox"/> MEODF Diffusing <input type="checkbox"/> MEOBW Batwing <input type="checkbox"/> MEOGC Glare Control <input type="checkbox"/> MEOWW Wall Wash PRO* <input type="checkbox"/> PROAY Asymmetric <input type="checkbox"/> PROWD Wide <input type="checkbox"/> PRONR Narrow *PRO Optics are only available in 90+ CRI *PRO Optics are not a diffused light source. LED pixelation will be seen with this optic choice. See page 4 for details.	<input type="checkbox"/> ULL Low (193 l/ft @ 1.84 W)* <input type="checkbox"/> UML Medium (477 l/ft @ 4.55 W)* <input type="checkbox"/> UHL High (940 l/ft @ 9.46 W)* <input type="checkbox"/> SLO-xx **Specified Lumen Output available. *Delivered lumen output & consumed wattage based on "MEODF 835" (80 CRI - 3500K). See SLO Configurator for alternate outputs. **See SLO Configurator at ExtantLighting.com for appropriate "xx" output.	MEO <input type="checkbox"/> MEODF Diffusing <input type="checkbox"/> MEOBW Batwing <input type="checkbox"/> MEOGC Glare Control PRO* <input type="checkbox"/> PROAY Asymmetric <input type="checkbox"/> PROWD Wide <input type="checkbox"/> PRONR Narrow *PRO Optics are only available in 90+ CRI *PRO Optics are not a diffused light source. LED pixelation will be seen with this optic choice. See page 4 for details.	80+ CRI <input type="checkbox"/> 830 3000K <input type="checkbox"/> 835 3500K <input type="checkbox"/> 840 4000K 90+ CRI <input type="checkbox"/> 927 2700K <input type="checkbox"/> 930 3000K <input type="checkbox"/> 935 3500K <input type="checkbox"/> 940 4000K <input type="checkbox"/> XX Optional Color Temp & CRI Available	<input type="checkbox"/> VU 120V-277V <input type="checkbox"/> V3 347V <input type="checkbox"/> V1 120V (for DL2 Driver only)


Driver	Finish	Options	Mounting
<input type="checkbox"/> D_ 1% 0-10V <input type="checkbox"/> DN NON DIM <input type="checkbox"/> DL5 Lutron 5-Series EcoSystem <input type="checkbox"/> DL1 Lutron Hi-Lume 1% EcoSystem <input type="checkbox"/> DL2 Lutron Hi-Lume 1% 2-wire (120V only) <input type="checkbox"/> DE* .1% 0-10V <input type="checkbox"/> DD1 1% DALI <input type="checkbox"/> DDE .1% DALI <input type="checkbox"/> XX Other (Please Specify) *Dim to Off available. Please Specify "-OFF" next to driver option if required. *1% minimum dimming level and other custom dimming levels and settings available. Consult factory.	<input type="checkbox"/> SA* Silver Anodized <input type="checkbox"/> WP* Matte White <input type="checkbox"/> BP* Matte Black <input type="checkbox"/> CC* Custom *When above finish selected, the housing finish and end cap finish will match <input type="checkbox"/> SAMF SA Housing/Machine Finish End Caps <input type="checkbox"/> WPMF WP Housing/Machine Finish End Caps <input type="checkbox"/> BPMF BP Housing/Machine Finish End Caps <input type="checkbox"/> CCMF CC Housing/Machine Finish End Caps	<input type="checkbox"/> EMB_* Emergency Battery Pack(s) <input type="checkbox"/> EMC_* Emergency Circuit(s) <input type="checkbox"/> SOC* Occupancy Sensor <input type="checkbox"/> SDL* Daylight Sensor <input type="checkbox"/> 2C 2 Circuit (Direct Light and Indirect Light (Controlled Independently)) <input type="checkbox"/> BCS* Brilliant Communications Solutions (wired/wireless) BCS: includes wired and wireless integration from our partners at nLight™, enlightened, Legrand, Crestron, Osram, Lutron and many more. Contact Extant for details. EMB: Specify quantity of battery packs. Minimum 4' unit. EMC: Specify quantity of emergency circuits. SOC & SDL: Specify spacing/location of sensors(s).	<input type="checkbox"/> AC Aircraft Cable <input type="checkbox"/> AR *Aircraft Cable Rotational (1" Rotational Hub) *Finish will match end caps

Cable Length	Power Cord	Canopy Mounting	Canopy Shape/Finish
<input type="checkbox"/> 24 24" <input type="checkbox"/> 48 48" <input type="checkbox"/> 72 72" <input type="checkbox"/> 96 96" <input type="checkbox"/> 144 144" <input type="checkbox"/> ___ * Custom Length (Please Specify)	<input type="checkbox"/> SL Silver <input type="checkbox"/> WH White <input type="checkbox"/> BK Black	REMOTE DRIVER OPTION <input type="checkbox"/> C5 5" Canopies - JBox (Standard) <input type="checkbox"/> NC No Canopies at all Cables <input type="checkbox"/> C2 2" Canopies at all Cables - Structure Mounting INTEGRAL DRIVER OPTION <input type="checkbox"/> C5 5" Canopies - JBox (Standard) <input type="checkbox"/> NC5 No Canopies at all Cables Except 5" at Power Feed <input type="checkbox"/> NC No Canopies at all Cables <input type="checkbox"/> C2 2" Canopies at all Cables - Structure Mounting	<input type="checkbox"/> SQS Square Silver <input type="checkbox"/> SQW Square Matte White <input type="checkbox"/> SQB Square Matte Black <input type="checkbox"/> RNS Round Silver <input type="checkbox"/> RNW Round Matte White <input type="checkbox"/> RNB Round Matte Black

EXTANT EXPRESS 9 - DAY SHIPPING
HIGHLIGHTED ORDERING INFO QUALIFIES
Max 500'. For more details, visit ExtantLighting.com




Dimensions




Patterns


R__X__
Rectangle
Provide Ax B
Example: R6'x4'



U__X__X__
U-Shape
Provide Ax BxC
Example:
U6'x4'x4'



L__X__
L-Shape
Provide Ax B
Example: L6'x4'



Note: All miters/patterns shown and ordered in Plan View.

Specifications

Construction One-piece heavy gauge 6063 extruded aluminum housing. Precision-machined aluminum end caps.

Optics Microstructure EdgeTech Optics (MEO)[™] utilizes high efficiency microstructure lenses and light guide plates for high optical extraction and precise light management. Specify Batwing, Glare Control, Diffused (Lambertian), or Wall Wash Optics.

Light Output(3) Standard individually controlled (Indirect & Direct) lumen packages are available: Low (ULL/DLL), Medium (UML/DML) and High (UHL/DHL). Specified Lumen Output (SLO) packages available. Please see the (SLO) configurator at ExtantLighting.com.

LEDs Latest generation of premium Nichia 3-step MacAdam Ellipse LED's available in (90+ CRI) 2700K, 3000K, 3500K, 4000K or (80+ CRI) 3000K, 3500K or 4000K. LED modules are easily accessible and replaceable.

Voltage Universal 120/277V (VU) and 347V (V3) available. Consult factory for driver options when 347V is specified.

Emergency Battery Factory provided low profile 10W emergency battery for UL924 required 90-minute run time (optional).

Finish Standard finishes include silver anodized, powder coated white or powder coated black. Custom anodized and powder coated finishes available (RAL number matched). Power cord and canopy finishes are white, black or silver.

Continuous Rows Innovative toolless latch system ensures simple installation. Seamless continuous rows with no lens breaks, pixilation or hotspots up to 400 feet with MEODF or 250 feet with MEOGC.

Patterns Standard Rectangle Pattern (R), U Pattern (U), and L Pattern (L) available. Custom patterns available.

Mounting Remote Driver Fixtures: Adjustable 3/64" Aircraft Cable or 361° locking 3/64" Aircraft Cable Rotational with precision-machined 1" rotational hub. Integral Driver Fixtures: Adjustable 1/16" Aircraft Cable and 1/16" Aircraft Cable Rotational with precision-machined 1" rotational hub.

Approvals UL and cUL Listed. Approved for Dry/Damp locations. Made in the USA

Lumen Maintenance (L70) 70% of initial light output = Reported > 60,000 hours | Calculated > 200,000 hours (L90) 90% of initial light output = Reported > 60,000 hours | Calculated > 200,000 hours.

Warranty HTG1 offered with a 5-year limited warranty. 5-year limited warranty covers LED, driver and fixture. For further details, refer to General Warranty and Obligations at ExtantLighting.com.

* Due to our culture of always striving for product enhancement, specifications and information within this document are subject to change without notice. 2020 Extant Lighting, Inc. All rights reserved.

Continuous Row Detail


NOTE: Detail below is specific to the Aircraft Cable (AC) with Integral Driver (TD) only. For additional Continuous Row Detail, please visit ExtantLighting.com

Nominal Row Length (ft)	Segment Lengths (ft)	Overall Row Length
9	5 + 4	9' 1/2"
10	6 + 4	10' 1/2"
11	7 + 4	11' 1/2"
12	8 + 4	12' 1/2"
13	8 + 5	13' 1/2"
14	8 + 6	14' 1/2"
15	8 + 7	15' 1/2"
16	8 + 8	16' 1/2"
17	8 + 5 + 4	17' 1/2"
18	8 + 6 + 4	18' 1/2"
19	8 + 7 + 4	19' 1/2"
20	8 + 8 + 4	20' 1/2"
21	8 + 8 + 5	21' 1/2"
22	8 + 8 + 6	22' 1/2"
23	8 + 8 + 7	23' 1/2"
24	8 + 8 + 8	24' 1/2"
25	8 + 8 + 5 + 4	25' 1/2"
26	8 + 8 + 6 + 4	26' 1/2"
27	8 + 8 + 7 + 4	27' 1/2"
28	8 + 8 + 8 + 4	28' 1/2"
29	8 + 8 + 8 + 5	29' 1/2"
30	8 + 8 + 8 + 6	30' 1/2"
31	8 + 8 + 8 + 7	31' 1/2"
32	8 + 8 + 8 + 8	32' 1/2"
33	8 + 8 + 8 + 5 + 4	33' 1/2"
34	8 + 8 + 8 + 6 + 4	34' 1/2"
35	8 + 8 + 8 + 7 + 4	35' 1/2"
36	8 + 8 + 8 + 8 + 4	36' 1/2"
37	8 + 8 + 8 + 8 + 5	37' 1/2"
38	8 + 8 + 8 + 8 + 6	38' 1/2"
39	8 + 8 + 8 + 8 + 7	39' 1/2"
40	8 + 8 + 8 + 8 + 8	40' 1/2"
41	8 + 8 + 8 + 8 + 5 + 4	41' 1/2"
42	8 + 8 + 8 + 8 + 6 + 4	42' 1/2"
43	8 + 8 + 8 + 8 + 7 + 4	43' 1/2"
44	8 + 8 + 8 + 8 + 8 + 4	44' 1/2"
45	8 + 8 + 8 + 8 + 8 + 5	45' 1/2"
46	8 + 8 + 8 + 8 + 8 + 6	46' 1/2"
47	8 + 8 + 8 + 8 + 8 + 7	47' 1/2"
48	8 + 8 + 8 + 8 + 8 + 8	48' 1/2"



Microstructure EdgeTech Optics (MEO)[™]

Our innovative MEO[™] design utilizes high efficiency microstructure lenses and light guide plates for high optical extraction and precise light management. MEO[™] delivers exceptional light quality with seamless illumination and uniformity with no pixelation, hot spots and lens breaks up to 400' continuous rows.



Precision Refractive Optics (PRO)

Precision Refractive Optics (PRO) are designed to produce precise optic control for diverse design applications. PRO utilizes the latest in extruded lens technology that mount directly to the LED board channel to give optimum control.

Please Note: The PRO optics are not a diffused light source. LED pixelation will be seen with this optic choice. If you want a completely diffused light source with no pixelation or hot spots, see our Microstructure EdgeTech Optics (MEO)[™] options.

